



TANDBERG

1700 MXP

Personal Telepresence (Up to approx. 1-2 persons)



Personal telepresence designed for the office, the 1700 features a superior HD camera and a widescreen LCD. This fully integrated system enables seamless face-to-face telepresence collaboration right at the desktop.

DESIGN FEATURES

- All-in-one executive control center designed for offices
- Compact HD Camera
- Integrated 20" widescreen LCD
- Powerful presentation, multimedia and conferencing capabilities

APPLICATION FEATURES

- Join up to 4 video sites and 3 audio sites with embedded MultiSite functionality
- Best possible call for each MultiSite participant with rate matching and transcoding
- Powerful live presentations through one-step PC plug-in
- View presentations and presenter simultaneously
- TANDBERG Expressway Technology
- URI Dialing

PERFORMANCE FEATURES

- Up to 2 Mbps H.323/2 Mbps SIP/2.3 Mbps total Multisite
- Highest level of embedded encryption as well as H.235 and IEEE 802.1x authentication
- True CD-quality audio
- Protection against network interruptions in point-to-point and multipoint calls with automatic Downspeeding and IPLR
- Superior video quality incorporating the H.264 standard

Get the most from your investment with VisionsConnected professional services. VisionsConnected experts support deployment of complex video infrastructures, installation, configuration and usage & adoption. Visit www.visionsconnected.com for more information.

VISIONS
CONNECTED 

TANDBERG

1700 MXP – Personal Telepresence

UNIT DELIVERED COMPLETE WITH:

Integrated HD Camera with camera cover, 20" Widescreen LCD, wireless remote control, microphone and cables

LCD SCREEN

Widescreen LCD (16:9)
Wide view angle screen
WXGA; 1366 x 768
Auto or manual brightness

BANDWIDTH

H.323 up to 2 Mbps
SIP up to 2 Mbps

Firewall Traversal

TANDBERG Expressway Technology™
Auto NAT
H.460.18, H.460.19 Firewall Traversal

VIDEO STANDARDS

H.261, H.263, H.263+, H.263++ (Natural Video), H.264

VIDEO FEATURES

Native 16:9 Widescreen
Advanced Screen Layouts
Picture in Picture (PIP)
Picture outside Picture (POP) & Large POP
Side by Side
PC Zoom
Intelligent Video Management
Local Auto Layout

VIDEO INPUTS

1 x DVI-I/SXGA: PC
PC using VNC (SoftPresenter)
1 x DVI-I: PC
Input: 800 x 600 (@ 60, 72, 75, 85 Hz), 1024 x 768 (@ 60, 70, 75 Hz), 1280 x 720 (HD720P) (@ 50, 60 Hz), 1280 x 1024 @ 60/Hz
Extended Display Identification Data (EDID)

VIDEO FORMAT

NTSC, PAL, VGA, SVGA, XGA, W-XGA, SXGA and HD720p

LIVE VIDEO RESOLUTIONS

NATIVE NTSC:
400p (528 x 400 pixels)
4SIF (704 x 480 pixels), Digital Clarity
Interlaced SIF (SIF 352 x 480 pixels), Natural Video
SIF (352 x 240 pixels)
NATIVE PAL:
448p (576 x 448 pixels)
4CIF (704 x 576 pixels), Digital Clarity
Interlaced CIF (CIF 352 x 576 pixels), Natural Video
CIF (352 x 288 pixels)
QCIF (176 x 144 pixels)
SQCIF (128 x 96 pixels) decode only
NATIVE PC RESOLUTIONS:
XGA (1024 x 768 pixels)
SVGA (800 x 600 pixels)
VGA (640 x 480 pixels)
WIDE RESOLUTIONS:
w288p (512 x 288 pixels)
w448p (768 x 448 pixels)
w576p (1024 x 576 pixels)
w720p (1280 x 720 pixels)

STILL IMAGE TRANSFER

CIF, SIF, 4CIF (H.261 Annex D), 4SIF, VGA, SVGA, XGA

AUDIO STANDARDS

G.711, G.722, G.722.1, G.728, 64 bit & 128 bit MPEG4 AAC-LD

AUDIO FEATURES

CD-Quality 20 KHz Mono and Stereo
Telephone add-on via MultiSite
Two separate acoustic echo cancellers
Audio mixer
Automatic Gain Control (AGC)
Automatic Noise Reduction
Audio level meters
Packet loss management
Active lip synchronization
GSM interference audio feature

PRIVACY FEATURE

Headset Microphone: 3.5mm Jack
Headset loudspeaker: 3.5mm Stereo Jack

FRAME RATES

30 frames per second @ 168 kbps and above
60 fields per second @ 336 kbps and above (Point-to-point)

DUAL STREAM

DuoVideo
H.239 dual stream
Dynamic bandwidth adjustment (H.323)
Available on H.323, H.320 & SIP
Available in MultiSite from any site
BFCP

NETWORK FEATURES

SIP
Downspeeding
Programmable network profiles
Intelligent Call Management

MULTISITE FEATURES

H.323/SIP/Telephony/VoIP in the same conference
Audio and Video Transcoding
Video rate matching from 56 kbps — maximum conference rate
CP4 and Voice Switched
Best Impression (Automatic CP Layouts)
H.264, Encryption, Digital Clarity
Dual Stream from any site
ISDN & IP Downspeeding and IPLR
MultiSite (H.243) Cascading on H.323
Unicode H.243 Terminal Names
Dial in/Dial out
Chair control for host system
Snapshot of ongoing conference (JPEG)
Snapshot of ongoing DuoVideo/H.239 presentation (JPEG)
Separate welcome page for encrypted conferences
Conference rates up to 2.3 Mbps
Up to 4 video and 3 audio sites
4 sites @ 768 kbps (+telephone calls)
Multiway (Beta)

EMBEDDED ENCRYPTION

H.323, H.320 & SIP point-to-point and multipoint calls
Standards-based: H.233, H.234, H.235 v2&v3, DES and AES
NIST-validated AES
NIST-validated DES
Automatic key generation and exchange
Supported in Dual Stream & MultiSite

IP NETWORK FEATURES

IEEE 802.1x/EAP Network Authentication
H.235 Gatekeeper Authentication
DNS lookup for service configuration
Differentiated Services (DiffServ)
Resource Reservation Protocol (RSVP)
IP precedence
IP type of service (ToS)
IP adaptive bandwidth management (including flow control)
Auto gatekeeper discovery
Dynamic playout and lip-sync buffering
Intelligent Packet Loss Recovery (IPLR)
H.245 DTMF tones in H.323
Cisco CallManager integration using ECS
IP Address Conflict Warning
Date and Time support via NTP
Call Services

IPv6 NETWORK SUPPORT

Dual Stack IPv4 and IPv6 simultaneous support
N et service support on IPv6: Telnet, SSH, HTTP, HTTPS, ftp, SNMP, DNS, NTP, DHCP
Media support on IPv6: H.323, SIP, Streaming

SECURITY FEATURES

Management via HTTPS and SSH
IP Administration Password
Menu Administration Password
Dialling Access code
Streaming password
H.243 MCU Password
VNC password
SNMP security alerts
Disable IP services
MD-5 Challenge
Network Settings protection
SIP Authentication via NTLM
SIP Authentication via Digest
FIPS Mode

NETWORK INTERFACES

Internal 2 port Ethernet switch
1 x LAN/Ethernet (RJ-45) 10/100 Mbit for PC
1 x LAN/Ethernet (RJ-45) 10/100 Mbit (LAN/DSL/cable modem)
1 x USB for future usage

ETHERNET/INTERNET/INTRANET CONNECTIVITY

T CP/IP, DHCP, ARP, FTP, Telnet, HTTP, HTTPS, SOAP and XML, MD-5 Challenge
SNMP Enterprise Management
Internal web server
Internal streaming server

OTHER MAJOR STANDARDS SUPPORTED

H.231, H.233, H.234, H.235 v2&v3, H.239, H.241, H.243, H.281, H.323, RFC 3261, RFC 2237, RFC 3264, RFC 3311, RFC 3550, RFC 2032, RFC 2190, RFC 2429, RFC 3407

CAMERA

1/3" CMOS 65° horizontal field of view
38° vertical field of view (monitor and camera tilt)
88° total vertical field of view (with monitor and camera tilt)
Manual focus
Automatic or manual brightness/whitebalance
Focus distance 0.3m–Infinity
1280 x 720 pixels progressive @ 30fps

PRESENTATIONS AND COLLABORATION

Natural Presenter Package including:
PC Presenter (DVI-I, SXGA in)
PC SoftPresenter
Digital Clarity & Native Formats
Advanced Video Layouts
Streaming compatible with Cisco IP/TV,
Apple QuickTime®, RealPlayer® v8 etc.

SYSTEM MANAGEMENT

Support for Local directories (My Contacts), Corporate Directory and Global Directory
Total management via embedded web server, SNMP, Telnet, SSH, FTP and SOAP
Remote software upload: via Web server, ftp server or ISDN
1 x RS-232 local control and diagnostics
Remote control and on-screen menu system
External Services from TMS

DIRECTORY SERVICES

Support for Local, Global and Dynamic Server Directories
Unlimited entries using Server directory* supporting LDAP and H.350
Unlimited number for Corporate directory (through by TMS)
400 number global directory
200 number local directory
16 dedicated MultiSite entries
Received Calls with Date and Time
Directories in Local Languages
Placed Calls with Date and Time
Missed Calls with Date and Time

17 SELECTABLE MENU LANGUAGES

Arabic, Simplified Chinese, Traditional Chinese, Danish, English, French, German, Italian, Japanese, Korean, Norwegian, Portuguese, Russian, Spanish, Suomi, Swedish and Thai
Chinese, Korean and Japanese Input Method Editor
Import Custom Language through TMS

CUSTOMIZED WELCOME SCREEN AND COMPANY LOGO

Picture JPEG (logo.jpg): Recommended maximum size is 704x576 for Welcome Screen and 352x288 for Encryption Required Screen

POWER

Auto-sensing power supply 100–250 VAC, 50–60 Hz/120W MAX

OPERATING TEMPERATURE AND HUMIDITY

0°C to 40°C (32°F to 104°F) ambient temperature
Up to 90% Relative Humidity (RH)

STORAGE AND TRANSPORT TEMPERATURE

-20°C to 60° (-4°F to 140°) at RH 10–90% (non-condensing)

UNIT DIMENSIONS

Height: 51.0 cm (20.1 inches)
Width: 50.0 cm (19.7 inches)
Depth: 16.0 cm (6.3 inches) Footprint: 35.4 cm (13.9 inches) wide x 16.0 cm (6.3 inches) deep
Weight: 9.90 kg (21.8 lbs)



**VISIONS
CONNECTED**

Netherlands

Visiting address

Naritaweg 114
1043 CA Amsterdam
The Netherlands

Mailing address

P.O. Box 59352
1040 KJ Amsterdam
The Netherlands

Phone +31 (0)20 618 8628

Fax +31 (0)20 618 8325

Email info@visionsconnected.com

Website www.visionsconnected.com

Europe Headquarters

Visions Connected Netherlands BV
Amsterdam, The Netherlands

UK Headquarters

Visions Connected United Kingdom
Bristol, United Kingdom

Middle East Headquarters

Visions Connected FZ-LLC
Dubai, United Arab Emirates