



TANDBERG

Edge 95

Turn every room into an video room (Up to approx. 6-8 persons)



Connect team members for more productive meetings with the TANDBERG Edge MXP Series. These easy-to-install units turn a meeting room with a flat screen into an interactive situation room for improved teamwork and accelerated decision-making.

DESIGN FEATURES

- Designed for medium to small meeting rooms
- Transforms a flat panel display into a high definition, interactive meeting space
- TANDBERG PrecisionHD Camera

APPLICATION FEATURES

- Join up to four video and three audio sites with optional embedded MultiSite and bandwidth capabilities
- Best possible call for each MultiSite participant with rate matching and transcoding
- Multiway intuitively and instantly integrates multiple party video calls utilizing a TANDBERGMCU and VCS
- Powerful live presentations through one-step PC plug-in or LAN connection
- View presentations and presenter simultaneously with DuoVideo and H.239 Dual Stream
- TANDBERG Expressway™ Technology
- URI dialing

PERFORMANCE FEATURES

- Choice of network: up to 512 kbps ISDN (H.320)/2 Mbps IP (H.323 or SIP)
- PC card slot for wireless LAN connection
- Highest level of embedded encryption as well as H.235 and IEEE 802.1x authentication
- True CD-quality audio
- Protection against network interruptions in point-to-point and multipoint calls with automatic downspeeding and IPLR
- Superior video quality incorporating the H.264 standard

Get the most from your investment with VisionsConnected professional services. VisionsConnected experts support deployment of complex video infrastructures, installation, configuration and usage & adoption. Visit www.visionsconnected.com for more information.

VISIONS
CONNECTED 

TANDBERG

Edge 95 – Turn every room into a video room

UNIT DELIVERED COMPLETE WITH:

Wireless remote control, TANDBERG PrecisionHD Camera, microphone and cables

BANDWIDTH

95 MXP:

H.323 up to 512 kbps
H.323 & SIP up to 2 Mbps

85 MXP:

H.323 up to 384 kbps
H.323 & SIP up to 1.1 Mbps

75 MXP:

H.323 up to 128 kbps
H.323 & SIP up to 768 kbps

FIREWALL TRAVERSAL

TANDBERG Expressway™ Technology
Auto NAT
H.460.18, H.460.19 Firewall Traversal
SIP ICE

VIDEO STANDARDS

H.261, H.263, H.263+, H.263++ (Natural Video), H.264

VIDEO FEATURES

Native 16:9 Widescreen
Advanced Screen Layouts
Picture in Picture (PIP)
Picture outside Picture & Large POP
Side by Side
PC Zoom
Intelligent Video Management
Simultaneous videoconference & local PC mode
Local Auto Layout

VIDEO INPUTS (5 INPUTS)

1 x 9 PimDSUB: HD Main Camera
1 x MiniDin, S-video: auxiliary y/document camera
1 x RCA/Phono, composite: document camera/aux
1 x RCA/Phono, composite: VCR
1 x DVI-I: PC
Input: 800 x 600 (@60, 72, 75, 85 Hz), 1024 x 768 (@60, 70, 75 Hz),
1280 x 720 (HD720P) (@ 50, 60 Hz), 1280 x 1024 @ 60 Hz,
1280x768, 1280x800, 1366x768, 1366x768 (@60 Hz)
Extended Display Identification Data (EDID)

VIDEO OUTPUTS (4 OUTPUTS)

1 x MiniDin, S-video: main monitor
1 x RCA/Phono, composite: main monitor or VCR
1 x RCA/Phono, composite: dual monitor or VCR
1xDVI-1/XGA: main or second monitor
XGA Output
800 x 600 @ 75 Hz, 1024 x 768 @ 60 Hz, 1280 x 768 (WXGA)
@ 60 Hz, 1280 x 720 (HD720p) @ 60 Hz, 1280x800 @ 60 Hz
VESA Monitor Power Management

VIDEO FORMAT

NTSC, PAL, VGA, SVGA, XGA, WXGA, SXGA and HD720p

LIVE VIDEO RESOLUTIONS

NATIVE NTSC:

400p (528 x 400 pixels)
4SIF (704 x 480 pixels), Digital Clarity
Standard SIF (SIF 352 x 480 pixels), Natural Video
SIF (352 x 240 pixels)

NATIVE PAL:

448p (576 x 448 pixels)
4CIF (704 x 576 pixels), Digital Clarity
Interlaced CIF (ICF 352 x 576 pixels), Natural Video
CIF (352 x 288 pixels)
QCIF (176 x 144 pixels)
SQCIF (128 x 96 pixels) decode only

NATIVE PC RESOLUTIONS:

XGA (1024 x 768)
SVGA (800 x 600 pixels)
VGA (640 x 480 pixels)
WXGA (1280x768)
WIDE RESOLUTIONS:
w288p (512 x 288 pixels)
w448p (768 x 448 pixels)
w576p (1024 x 576 pixels)
w720p (1280 x 720 pixels)

STILL IMAGE TRANSFER

CIF, SIF, 4CIF (H.261 Annex D), 4SIF, VGA, SVGA, XGA, WXGA

AUDIO STANDARDS

G.711, G.722, G.722.1, G.728, 64 bit & 128 bit MPEG4AAC-LD

AUDIO FEATURES

CD-Quality 20KHz Mono and Stereo
Telephone add-on via MultiSite
Two separate acoustic echo cancellers
Audio mixer
Automatic Gain Control (AGC)
Automatic Noise Reduction
Audio level meters
VCR ducking
Optional Stereo Package
Packet loss management
Active lip synchronization
CSM/BlackBerry interference audio feature
ALD (Assistive Listening Devices) support with acoustic
echo cancellation

AUDIO INPUTS (4 INPUTS)

2 x microphone, 24V phantom powered, XLR connector
1 x RCA/Phono, Line Level: auxiliary y (for VCR Stereo L)
1 x RCA/Phono, Line Level: VCR/DVD (Stereo R)

AUDIO OUTPUTS (2 OUTPUTS)

1 x RCA/Phono, S/PDIF (mono/stereo) or Analogue
Line Level: main audio or Analogue Stereo L
1 x RCA/Phono, Line Level: VCR or Analogue Stereo R

FRAME RATES

30 frames per second @ 168 kbps and above
60 fields per second @ 336 kbps and above (point-to-point)

DUAL STREAM

DuoVideo
H.239 dual stream
Dynamic bandwidth adjustment (H.323)
Available on H.323 & H.320
Available in MultiSite from any site (95 & 85 MXP only)

NETWORK FEATURES

Auto H.320/H.323 dialing
SIP
Downspeeding
Programmable network profiles
Intelligent Call Management
Maximum call length timer
Automatic SPD and line number configuration
(National ISDN, GR-2941-CORE)
SoftMux
H.331 Broadcast Mode
NATO standard KG194/KIV-7 encr yptor support t**
URI Dialing
Direct DNS dialing
y (IPLR)
H.245 DTMF tones in H.323
Cisco CallManager integration using ECS
IP Address Conflict Warning
Date and Time support t via NTP
Call Ser vices

IPv6 NETWORK SUPPORT

Dual Stack IPv4 and IPv6 simultaneous support t
Net ser vice support t on IPv6: Telnet, SSH, HTTP, HTTPS,
FTP, SNMP, DNS, NTP, DHCP**
Media support t on IPv6: H.323, SIP, Streaming

SECURITY FEATURES

Management via HTTPS and SSH
IP Administration Password
Menu Administration Password
Dialing Access code
Streaming Password
H.243 MCU Password
VNC Password
SNMP security aler ts
Disable IP ser vices
MD-5 Challenge
Network Settings protection
SIP Authentication via NTLM
SIP Authentication via Digest

NETWORK INTERFACES

4 x ISDN BRI (RJ-45), S-ster face
1 x LAN/Ethernet (RJ-45) 10/100 Mbit
(LAN/DSL/cable modem)
1 x PC card slot (PCMCIA) for wireless LAN
1 x USB for future usage

WIRELESS LAN SUPPORT

Compliant with IEEE 802.11b, up to 11 Mbit
Support t for 64/128 bit encr yption (WEP)
Infrastructure or ad-hoc mode

ETHERNET/INTERNET/INTRANET CONNECTIVITY

TCP/IP, DHCP, ARP, FTP, Telnet, HTTP, HTTPS, SOAP and
XML, MD-5 Challenge
SNMP Enterprise Management
Internal web ser ver
Internal streaming ser ver

OTHER MAJOR STANDARDS SUPPORTED

H.231, H.233, H.234, H.235 v2&v3, H.239, H.241, H.243,
H.281, BONDING (ISO 13871), H.320, H.323, H.331
RFC 3261, RFC 2237, RFC 3264, RC 3311, RFC 3550,
RFC 2032, RFC 2190, RFC 2429, RFC 3407

PRECISIONHD CAMERA

7 x zoom 1/3" CMOS +10°/-20° tilt +/- 90° pan
42° ver tical field of view
72° total ver tical field of view
70° horizontal field of view
250° total horizontal field of view
Focus distance 0.3m-infinity
1280 x 720 pixels progressive @ 30fps
Automatic or manual focus/brightness/whitebalance
Far-end camera control
15 near- and far-end camera presets
Voice-activated camera positioning
Daisy-chain support t (Visca protocol camera)

CLOSED CAPTIONING/TEXT CHAT

T.140 text chat available from Telnet, Web and User Interface

PRESENTATIONS AND COLLABORATION

Natural Presenter Package including:
PC Presenter (DVI-I, SXGA In)
PC SoftPresenter
Digital Clarity & Native Formats
Advanced Video Layouts
Streaming compatible with Cisco IP/TV,
Apple QuickTime®, RealPlayer® v8, etc.

SYSTEM MANAGEMENT

Support t for the TANDBERG Management Suite
Total management via embedded web ser ver, SNMP,
Telnet, SSH, FTP and SOAP
Remote software upload: via web ser ver, FTP ser ver or ISDN
1 x RS-232 local control and diagnostics
Remote control and on-screen menu system
External Ser vices from TMS

DIRECTORY SERVICES

Support t for Local Directories (My Contacts),
Corporate Director y and Global Director y
Unlimited entries using Ser ver director y* support ting
LDAP and H.350
Unlimited number for Corporate director y (through TMS)
400 number global director y
200 number local director y
16 dedicated MultiSite entries
Directories in Local Languages
Received Calls with Date and Time
Placed Calls with Date and Time
Missed Calls with Date and Time

17 SELECTABLE MENU LANGUAGES

Arabic, Simplified Chinese, Traditional Chinese, Danish, English,
French, German, Italian, Japanese, Korean, Norwegian,
Portuguese, Russian, Spanish, Suomi, Swedish and Thai
Chinese, Korean and Japanese Input Method Editor
Impor t Custom Language through TMS

CUSTOMIZED WELCOME SCREEN AND COMPANY LOGO

Picture JPEG (logo.jpg): Recommended maximum size
is 704x576 for Welcome Screen and 352x288 for
Encr yption Required Screen.

POWER

Auto-sensing power supply
100–250 VAC, 50–60 Hz
40 watts max

OPERATING TEMPERATURE AND HUMIDITY

0° C to 35° C (32° F to 95° F) ambient temperature
-20° C to 60° C (-4° F to 140° F) at RH 10–90%
(non-condensing)

STORAGE AND TRANSPORT TEMPERATURE

-20° C to 60° C (-4° F to 140° F) at RH 10–90%
(non-condensing)

APPROVALS

Directive 73/23/EEC (Low-Voltage Directive)
– Standard EN 60950
Directive 89/336/EEC (EMC Directive)
– Standard EN 55022, Class B
– Standard EN 55024
– Standard EN 61000-3-2/-3-3
Directive 1999/5/EEC (R&TTE Directive)
– Standard TBR3
Approved according to UL 60950 and CAN/CSA C22.2
No.60950
Complies with FCC15B Class B

UNIT DIMENSIONS

Height: 16.9"/42.9cm
Width (including footstand): 5.7"/14.5cm
Depth (including footstand): 9.0"/22.8cm
Weight: 7.7 lbs/3.5 kg

VISIONS
CONNECTED

Netherlands

Visiting address

Naritaweg 114
1043 CA Amsterdam
The Netherlands

Mailing address

P.O. Box 59352
1040 KJ Amsterdam
The Netherlands

Phone +31 (0)20 618 8628

Fax +31 (0)20 618 8325

Email info@visionsconnected.com

Website www.visionsconnected.com

Europe Headquarters

Visions Connected Netherlands BV
Amsterdam, The Netherlands

UK Headquarters

Visions Connected United Kingdom
Bristol, United Kingdom

Middle East Headquarters

Visions Connected FZ-LLC
Dubai, United Arab Emirates